

PROTECTIVE HEADWEAR



Replacement Integrated Shield for EVO® VISTAshield®

AMV200-000-000



DESCRIPTION

Replacement Integrated Anti Mist Anti Scratch KN Shield for EVO®VISTAshield® Helmet.

SAFETY STANDARDS

AS/NZS1337

FEATURES

When fitted to the EVO®VISTAshield® Helmet this replacement shield has the following features and benefits -

- Optical Class 1 - High optical quality with no optical distortion.
- K Rated - Anti-Scratch resistance to surface damage from fine particles.
- N Rated - Anti-Mist resistance to fogging.
- A - Impact Rating. High energy impact; 6mm, 0.86g ball travelling at 425mph (685kph).
- UV 2C-1.2 2: UV filter (EN170) provides protection from harmful UV. C: Unimpaired colour perception. 1.2: High light transmission.

SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN

filtering effect Scale Number
2C



Manufacturer's Trademark
JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball
@ 190 m/s Maximum protection for face shields
A



Resistance to Surface Damage by Fine Particles
(optional)
K



Visor Length
12.5cm



Recyclable
Yes



BSI Kitemark
Yes



LIGHT TRANSMISSION BREAKDOWN

Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 –Class 2 – Medium quality for occasional use. 3 – Class 3 –Low quality for exceptional use)



1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional



T



Resistance to fogging (optional)

N

Material
Polycarbonate



Product Weight
103g