

EVO® ALTA™ Skyworker™

ARC170-000-1AN / ARC170-001-6AN / ARC170-001-1AN



White | ARC170-000-1AN



Orange | ARC170-001-6AN



Black | ARC170-001-1AN

DESCRIPTION

The new EVO® ALTA™ offers all-round impact protection. Featuring a specialised shell structure and internal liner to increase durability and shock absorption performance.

EVO® ALTA™ Skyworker™ is certified to the EN 12492 mountaineering helmet standard with a 4-point chinstrap designed to stay secure under force, maximising security during a fall.

Precise adjustment settings enable a secure fit, ensuring the helmet remains stable.

Engineered to maximise compatibility and accessory integration, EVO® ALTA™ is an adaptive system with built-in attachment points and an interchangeable front module.























SAFETY STANDARDS

- EN 12492
- AS/NZS1801

FEATURES

- EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.
- The EVO® ALTA™ range maximises compatibility and accessory integration. Attachment points on the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.
- The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands for protection against heat stress.
- The 4-point chinstrap is easy to adjust. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.
- Side and rear ventilation in the helmet's shell and liner reduce temperatures by an average of 2-3 degrees.
- EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.
- Featuring an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.
- The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.
- Helmets can be customised to meet a corporate identity. Logo printing is available on the front and sides of this safety helmet, helping to increase brand recognition and discourage theft. MOQs apply.

SPECIFICATIONS

	Peak Micro		Impact Resistance 100 Joules
	Side Impact Resistance 25 Joules		Molten Metal Meets performance requirements
	Lateral Deformation Meets performance requirements		EN 50365 ELECTRICAL INSULATION Meets performance requirements
	Maximum Temperature +50°C		Minimum Temperature -40°C
	ABS Shell Yes		EPP Liner Yes
	Recyclable Shell		Textile Harness
	Ventilation Yes		Depth Adjustment 3D Harness
	Wheel Ratchet Yes		Fitted 4 point chinstrap (EN12492 Compliant) Fitted
	Universal Accessories Slot Yes		Reflective Option Optional
	ID card holder Optional		JSPCheck Yes
	Product Weight 500g		Size 53-64cm