

# ELEVATED WORK PLATFORM (EWP) HARNESS C/W PERMANENTLY ATTACHED LANYARD



HEIGHT  
SAFETY

PART CODE: **H101-L15SN** (LENGTH+HARDWARE)

## PRODUCT FEATURES >

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- Large Dorsal D Ring for easier connection.
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head.
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- Service Pouch on back.

## APPLICATIONS >

Fall Arrest, Construction, Ladder, Scaffolding, Elevated Work Platforms, Warehouse.

## STANDARDS >



AS/NZS 1891.1:2020  
BMP 713822  
BMP 713823  
Australian Standard



AS/NZS 1891.5:2020  
BMP 745726  
BMP 745728  
Australian Standard



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

**PARAMOUNT SAFETY PRODUCTS AUSTRALIA**  
12 FELLOWSHIP ROAD,  
GNANGARA, WA 6077  
TECH SUPPORT: 1300 546 747  
CUSTOMER SERVICE: 1300 770 723  
EMAIL: INFO@PARAMOUNTSAFETY.COM

**PARAMOUNT SAFETY PRODUCTS NEW ZEALAND**  
7 SIR WOOLF FISHER DRIVE, HIGHBROOK,  
EAST TAMAKI, AUCKLAND 2013  
TECH SUPPORT: 0800 546 747  
CUSTOMER SERVICE: 0800 888 778  
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQS.COM  
PARAMOUNTSAFETY.COM



# ELEVATED WORK PLATFORM (EWP) HARNESS C/W PERMANENTLY ATTACHED LANYARD



HEIGHT  
SAFETY


PART CODE: **H101-L15SN** (LENGTH+HARDWARE)

## PRODUCT DETAILS >

- AUS/NZ designed and engineered
- Size ranges available - Small, Standard (M-L) and Maxi (XL-2XL)
- 10-year life span from date of manufacture




DORSAL  
D RING



PASS  
THROUGH  
2BAR / 3BAR  
BUCKLE  
SYSTEM



FRONT FALL  
ARREST  
ATTACHMENT  
POINTS



RETRO  
REFLECTIVE  
THREAD



## TECHNICAL INFORMATION >

- **Webbing Material:** Polyester; 45mm; UV Resilient
- **Fall Arrest Hardware:** Drop Forged corrosion resistant electrophoresis; high tensile steel
- **Thread:** Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- **Stitch Pattern:** THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- **Plastic Material:** UV stabilised high-density polyethylene
- **Weight:** 1.95kg
- **Web Tenacity:** 28kN
- **Drop Forged D Rings:** Alloy Steel (standard): 40kN
- **Buckle Strength:** 12 to 17kN model dependent. Laser etched or hard marked on buckle
- **Padding Material:** Neoprene laminate

## ACCESSORIES >

- **KS:** Karabiner Screw Gate Steel Alloy 18mm
- **KD:** Karabiner Double Action Steel Alloy 19mm
- **KT:** Karabiner Triple Action Steel Alloy 26mm
- **KTS:** Karabiner Triple Action Stainless Steel 27mm
- **SD:** Scaffold Hook Double Action Steel Alloy 68mm
- **ST:** Triple Action Scaffold Hook Steel Alloy 68mm
- **SN:** Snap Hook

Note: Product code is made up of length + hardware.

**H101-L15SN:** H101 Harness + 1.5 Length Lanyard + Snap Hook

## LANYARD DETAILS >

- Webbing Tenacity = 28kN
- Webbing is UV rated to meet AS 1891.5:2020 standard.
- THETA stitch pattern is engineered to match webbing strength to ensure no weak point in the harness assembly.
- Contrast stitch thread colour for easy inspection.
- Standard LINQ shock absorber is rated for wearer of up to 150kg. Including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- Custom lengths available on request for example: 1.0m, 1.2m, 1.5m, 1.8m, 2.0m.

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

**PARAMOUNT SAFETY PRODUCTS AUSTRALIA**  
12 FELLOWSHIP ROAD,  
GNANGARA, WA 6077  
TECH SUPPORT: 1300 546 747  
CUSTOMER SERVICE: 1300 770 723  
EMAIL: INFO@PARAMOUNTSAFETY.COM

**PARAMOUNT SAFETY PRODUCTS NEW ZEALAND**  
7 SIR WOOLF FISHER DRIVE, HIGHBROOK,  
EAST TAMAKI, AUCKLAND 2013  
TECH SUPPORT: 0800 546 747  
CUSTOMER SERVICE: 0800 888 778  
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQHS.COM  
PARAMOUNTSAFETY.COM

