## PREMIUM GT HARNESS: RIGGERS

**PART CODE: H802GT** 



- Premium LINQFlex webbing for extra comfort with up to 9% stretch which allows for more range and movement.
- Lightweight aluminium Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- · Confined Space Rescue Loops.
- Comes with Suspension Trauma Strap: One-piece Webbing with a quick connection buckle for faster deployment and connection in the event of a fall.
- · Cam adjusters for quick adjustment.
- · Padded Legs for force dispersion at moment of fall impact.
- Air COOL Padded Shoulder Straps for increased comfort and increased air flow.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- · Aluminium Quick Release Buckles.
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall.
- · GT harness bag.
- · Service Pouch on back.
- Large Pole strap Side D's for ease of connecting Pole Strap (work positioning).
- · Adjustable Waist Belt with tool loop attachments.

### **APPLICATIONS** >

Construction and Scaffolding, Rigging, Warehouse and Ladder Work.

#### STANDARDS >









Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.







# PREMIUM GT HARNESS: RIGGERS

**PART CODE: H802GT** 



### PRODUCT DETAILS >

- · AUS/NZ designed and engineered
- · Size ranges available: M XL and 2XL
- 10-year life span from date of manufacture



REAR DORSAL D RING



QUICK RELEASE BUCKLES



**BELAY LOOPS** 



**RELIEF STEP** 



**CAM ADJUSTERS** 



**GT HARNESS BAG** 

### **TECHNICAL INFORMATION** >

- · Webbing Material: Polyester; 45mm; UV Resilient
- Buckle Material Upper Body: Corrosion resistant silver galvanised; high tensile steel
- Buckle Material Lower Body: Aluminum
- Thread: Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength
- · Weight: 2.5kg
- · Web Tenacity: 28kN
- · Drop Forged O Rings: Alloy Steel; 40kN
- Buckle Strength: 12 to 17kN. Laser etched or hard marked on buckle
- · Padding Material: UV stabilised high-density polyethylene

