

PREMIUM GT HARNESS: TOWER

PART CODE: **H902GT**



**HEIGHT
SAFETY**

PRODUCT FEATURES >

- Premium LINQFlex webbing for extra comfort with up to 9% stretch which allows for more range and movement.
- Lightweight aluminium Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- Confined Space Rescue Loops.
- Comes with Suspension Trauma Strap: One-piece Webbing with a quick connection buckle for faster deployment and connection in the event of a fall.
- Cam adjusters for quick adjustment.
- Padded Legs for force dispersion at moment of fall impact.
- Air COOL Padded Shoulder Straps for increased comfort and increased air flow.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- Aluminium Quick Release Buckles.
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall.
- GT harness bag.
- Service Pouch on back.
- Large Pole strap Side D's for ease of connecting Pole Strap (work positioning).
- Adjustable Waist Belt with tool loop attachments.
- Forward placed pole strap attachment points makes for easier to reach connection.
- Padded Sub Pelvic Seat for Pole Strap restraint High Comfort spec.
- Large Pole strap O-rings for ease of connecting Pole Strap (work positioning).



APPLICATIONS >

Tower Work, Linesman Positioning, Working at Heights where Suspension is Required.

STANDARDS >



AS/NZS 1891.1:2020
BMP 713822
BMP 713823
Australian Standard



**Working
at Height
Association**
Reaching new levels in safety



**LINQ
TEST
LAB
FACILITY**
WORLD RECOGNISED
ACCREDITATION

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

2/980 ABERNETHY ROAD,
HIGH WYCOMBE, WA 6057
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQHS.COM
PARAMOUNTSAFETY.COM



PREMIUM GT HARNESS: TOWER

PART CODE: **H902GT**



PRODUCT DETAILS >

- AUS/NZ designed and engineered
- Size ranges available: M - XL and 2XL
- 10-year life span from date of manufacture



**REAR DORSAL
D RING**



**QUICK RELEASE
BUCKLES**



**CONFINED SPACE
RESCUE LOOPS**



**POLE STRAP
O-RINGS**



BELAY LOOPS



GT HARNESS BAG



TECHNICAL INFORMATION >

- **Webbing Material:** Polyester; 45mm; UV Resilient
- **Buckle Material Upper Body:** Corrosion resistant silver galvanised; high tensile steel
- **Buckle Material Lower Body:** Aluminum
- **Thread:** Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- **Stitch Pattern:** THETA Pattern combines 313 stitches to exceed 28kN of strength
- **Weight:** 2.5kg
- **Web Tenacity:** 28kN
- **Drop Forged O Rings:** Alloy Steel; 40kN
- **Buckle Strength:** 12 to 17kN. Laser etched or hard marked on buckle
- **Padding Material:** UV stabilised high-density polyethylene