# DOUBLE LEG KERNMANTLE ADJUSTABLE ROPE LANYARD PART CODE: RLA2

### **PRODUCT INFORMATION** >

Kernmantle Rope Lanyard - 2 metre Lanyard w/ adjuster. RLA2- Double Leg Kernmantle Rope Lanyard with shock pack + hardware ( see list below)

# PRODUCT FEATURES >

- Kernmantle rope is rope constructed with its interior core protected by a woven exterior sheath designed to optimise strength, durability, and flexibility. The core fibers provide the tensile strength of the rope, while the sheath protects the core from abrasion during use.
- An exclusive Extended Length Energy Absorber ELEA) designed to protect a worker of up to 150kg, including tools and equipment.
- Drop forged lanyard hardware.
- Stitching patterns are sewn by computer controlled bar tacking machinery for precision using UV resistant high tenacity polyester yarn with 100 newton (10kg) breaking strength.

# PRODUCT DETAILS >

- AUS/NZ designed and engineered.
- 11.5mm kernmantle rope and rope grab 11 16mm.
- Standard LINQ shock absorber is rated for wearer of up to 150kg, including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- Custom lengths available on request, for example: 1.0m, 1.2m, 1.5m, 1.8m.
- Outer Casing Polyester
- Inner/Core Polyester
- Fall Arrest Hardware Drop Forged corrosion resistant electrophoresis; high strength alloy steel.
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast.

#### STANDARDS >







#### ACCESSORIES >

- KD : Karabiner Double Action Steel Alloy 19mm
- KS: Karabiner Screw Gate Steel Alloy 18mm
- KT: Karabiner Triple Action Steel Alloy 26mm
- KTS: Karabiner Triple Action Stainless Steel 27mm
- SD: Scaffold Hook Double Action Steel Alloy 68mm
- ST: Triple Action Scaffold Hook Steel Alloy 68mm
- SN: Snap Hook

Note: 1st hardware code listed is connected to the body. **RLA1KSRG** includes 1 x Screw Gate Karabiner & 1 x Rope Grab **RLA2KSRG** includes 1 x x Screw Gate Karabiner & 2 x Rope Grab



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.