

# G-TEK® POLYKOR® HI-VIS



PRODUCT CODE: 16-333HVY

**G-Tek**  
PolyKor®



## Product Information:

- G-Tek® PolyKor® Hi-Vis gloves designed for light to medium cut hazard risks with an EN388 Cut Rating Level C.
- High Visibility 13 gauge PolyKor® lightweight soft feel shell provides excellent dexterity and tactile sensitivity. Seamless construction offers increased comfort and breathability.
- Thicker flexible nitrile micro-surface coated palm and fingertips help extend the life of the glove and provide excellent abrasion resistance.
- Knit wrist helps prevent dirt and debris from entering the glove.

## Applications:

- Mining Resource
- Automotive
- Assembly Work
- Machinery Maintenance
- Building/Construction
- Glass Industry
- Metal Folding
- Engineering

## Available In:

PRODUCT CODE	UOM	MOQ	CTN QTY
16-333HVY-(SIZE 7 TO 11)	PAIR	12	72

## Performance Data:

ANSI Cut Level:	A3
EN 388 (2016):	4X43C
EN Abrasion Level:	4
EN Cut Level - Coup Test:	X
EN Tear Level:	4
EN Puncture Level:	3
EN Cut Level - TDM100 Test:	C

## Cut Performance New Test - ISO13997 Cut Test:

**Scale of A - F (F the Highest):** Once the test is completed the rating is shown as a letter (A - F), indicating the force the test sample could withstand.

NEWTONS	WEIGHT	PERFORMANCE LEVEL
≥30	(3.06KG)	F
≥22	(2.24KG)	E
≥15	(1.53KG)	D
≥10	(1.02KG)	C
≥5	(0.51KG)	B
≥2	(0.20KG)	A

Weights and Newtons of force are the downward pressure applied to new blade on each cut pass during test.

## Standards:



**PARAMOUNT**  
SAFETY PRODUCTS

PART OF THE GLOBAL FAMILY

PIPAUS.COM  
PARAMOUNTSAFETY.COM

AUSTRALIA  
TECH SUPPORT: 1300 275 820  
CUSTOMER SERVICE: 1300 770 723  
EMAIL: INFO@PARAMOUNTSAFETY.COM

NEW ZEALAND  
TECH SUPPORT: 0800 888 778  
CUSTOMER SERVICE: 0800 888 778  
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ