PRATT TOXIC SUBSTANCE STORAGE CABINET: **250L XL - 2 DOORS - 3 SHELVES**

PRATT INDOOR TOXIC SUBSTANCE STORAGE CABINETS **COMPLY WITH THE AUSTRALIAN & NEW ZEALAND** STANDARD AS/ NZS4452 "THE STORAGE AND HANDLING OF TOXIC SUBSTANCES".

This range of cabinets is for the storage of Toxic Substances in liquid or solid as classified by the United Nations criteria and the ADG Code for Dangerous Goods. These include chemicals such as: Alkaloids, Arsenic, Aniline, Cyanides, Mercury, Phenol - Solid, Trichloroethylene, etc.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 90mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Toxic Substance diamond and other decals applied.
- Optional additional shelves available.
- Includes set of rubber feet.

- WEIGHT: 230kg 250LXL - CAPACITY: - DOORS: 2

- SHELVES: 3 (Inc. Base Level)

5560-29S - EXTRA SHELF:







E	XTERNAL (MI	м)	INTERNAL (MM)				VOLUME CAPACITY	PER SHELF	TOTAL
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH		2L Winchester	30	90
1825	1440	585	1545	1350	495		4L Winchester	16	48
TF:						_	4L Round Can	14	42
NTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING. OR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT							20L Round Can	4	12

E	XTERNAL (MN	1)	INTERNAL (MM)			
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	
1825	1440	585	1545	1350	495	

NOT

CLEARANCE LOCATIONS.

3. AS/NZS 4452 SPECIFIES A MAXIMUM OF 25KG OR L FOR PACKAGING GROUP I & 50KG OR L FOR PACKAGING GROUP II TOXIC SUBSTANCES.