PRATT CORROSIVE SUBSTANCE STORAGE CABINET: METAL - 425L - 2 DOORS - 3 SHELVES

PRATT INDOOR CORROSIVE SUBSTANCE STORAGE **CABINETS COMPLY WITH AS3780 "THE STORAGE AND** HANDLING OF CORROSIVE SUBSTANCES".

This range of cabinets is for the storage of Corrosive Substances in liquid or solid as classified by the United Nations criteria and the ADG Code for Dangerous Goods. These include chemicals such as: Acids, Alkalis, Caustics, Sodium Hydroxide Solution, Hypochlorite Solution etc.

CORROSIVE SUBSTANCES MAX CAPACITY



FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 90mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Additional powder coating of the shelving and closing assembly for added protection.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Corrosive diamond and other decals applied.
- Optional additional shelves available.
- Internal opening latch as required by Standards.

- WEIGHT: 247kg - CAPACITY: 425L - DOORS:

- SHELVES: 3 (Inc. Base Level) - EXTRA SHELF: 5590PH-29S - EXTRATRAY: 5545PH-29TS



ULCOPACITY Construction of the Construction of	1 10	
VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	42	126
4L Winchester	24	72
4L Paint Can	20	60

6

EXTERNAL (MM)		INTERNAL (MM)			
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1825	1115	865	1545	1015	775



20L Round Can

NOTIC:

I. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE SEQUENTIAL CHASSIS ASSEMBLY.

2. FOR TOTAL EXTERNAL WIDTH, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS.

3. AS 3780 SPECIFIES A MAXIMUM OF 50KG OR L FOR PACKAGING GROUP I CORROSIVE SUBSTANCES

[&]amp; 250KG OR L FOR PACKAGING GROUP II.

4. CABINETS ARE DESIGNED FOR THE SAFE STORAGE OF CORROSIVES IN SEALED & CLOSED CONTAINERS.