PRATT ORGANIC PEROXIDE STORAGE CABINET: 100L - 2 DOORS - 1 SHELF

PRATT INDOOR ORGANIC PEROXIDE STORAGE CABINETS COMPLY WITH THE AUSTRALIAN STANDARD **AS2714 "THE STORAGE AND HANDLING OF ORGANIC** PEROXIDES".

This range of cabinets is for the storage of Organic Peroxides in liquid or solid as classified by the United Nations criteria and the ADG Code for Dangerous Goods. These include chemicals such as: Acetyl Acetone Peroxide, Methyl Ethyl Ketone Peroxides, Dibenzoyl Peroxide etc.

FEATURES & BENEFITS:

- Low profile under bench design.
- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 1 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Magnetic catches to hold doors in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handles.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection.
- Organic Peroxide diamond and other decals applied.
- Optional additional shelves available.
- Includes set of rubber feet.
- WEIGHT: 100kg
- 100L - CAPACITY:
- DOORS:
- 2 1 (Inc. Base Level) - SHELVES:
- EXTRA SHELF: 5535-295

| EXTERNAL (MM) | | | INTERNAL (MM) | | |
|---------------|-------|-------|---------------|-------|-------|
| HEIGHT | WIDTH | DEPTH | HEIGHT | WIDTH | DEPTH |
| 770 | 935 | 620 | 495 | 840 | 530 |

NOTE

1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING. 2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT

CLEARANCE LOCATIONS. 3. AS 2714 SPECIFIES A MAXIMUM OF 50KG OR L FOR TYPE B ORGANIC PEROXIDES.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TECH SUPPORT: 1300 133 226 CUSTOMER SERVICE: 1300 133 226 EMAIL: INFO@PRATTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 **CUSTOMER SERVICE: 0800 888 778** EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

| VOLUME CAPACITY | PER SHELF | TOTAL | |
|-----------------|-----------|-------|--|
| 2L Winchester | 18 | 18 | |
| 4L Winchester | 15 | 15 | |
| 4L Round Can | 12 | 12 | |
| 20L Round Can | 2 | 4 | |







