# PROTEUS 2 SAFETY GLASSES

PRODUCT DATA SHEET: 1900 | 1902





## **FEATURES AND BENEFITS**

- AquaShield Hardened Anti-Fog Technology
- Dust Guard D-i tech Frame provides dust and water protection
- Dual lens full frame for increase strength and impact resistance
- Optically correct distortion free lens
- Adjustable temples for optimal facial positioning and PPE integration
- Soft D-i Tech Arms to ensure a secure comfortable grip
- Cold Formable Arm for individual fit
- UV400 100% UV Protection- on Tinted Lens
- Certified Medium Impact Protection

## PRODUCT DETAILS

Lens Material: AS/NZS Medium Impact rated

Polycarbonate Base Curve 9

Lens Coating AquaShield Hardened Anti-Fog Hydrophilic Technology

Frame/Arms: Polycarbonate + TPR

Weight: 28g

# **APPLICATIONS**

The Pro Choice Safety Gear range of eye protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments. The Proteus Range of protective eyeware also incorporates excellent protection from dust and excellent integration with other PPE.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying, transportation.

# **CLEANING INSTRUCTIONS**

Clean with warm soapy water or mild lens cleaning solutions. Do not use alcohol based cleaning wipes/solutions as this may damage the lens coatings.

#### PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TEST SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM

#### PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ













**AVAILABLE IN** 

PRODUCT CODE	UOM	MOQ	CTN QTY
1900	EACH	12	144
1902	EACH	12	144

## **CARE INSTRUCTIONS**

Avoid exposure to liquids/solvents that may cause the lens to distort/craze as this may affect protection required.

Inspect prior to use for any pitted, crazed, damaged or heavily scratched lenses and replace if signs of deterioration appear.


For heavily soiled applications, wash under running water to remove excess grit and wipe clean with Pro Choice Safety Gear Lens Cleaning Wipes.

For product longevity store in a clean microfiber Pro Choice Safety Gear Spectacle Pouch.

# **STANDARDS**

#### CERTIFIED TO:

AS/NZS 1337.1:2010 SAI Global LICENSE NUMBER- SMK 40226



SMOKE LENS - CATEGORY 3 - 16% (Tv)
LUMINOUS TRANSMITTANCE OUTDOOR TINTED



