

HEARING PROTECTION

PROBULLET™ DISPOSABLE EARPLUGS | CORDED & UNCORDED

PRODUCT DATA SHEET: EPOU | EPOC



PRODUCT CODE:

EPOU

PRODUCT CODE:

EPOC



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors Class 5 SLC₈₀27dB.
- Hearing protection for noise levels to 112dB(A).
- Hi-vis orange for visual identification & compliance.
- Economical & convenient choice for work situations that demand a high degree of comfort, frequent changes or where hygiene presents a problem for re-usage.
- Smooth tapered shape for easy insertion into the ear canal.
- Range of pack sizes & dispensing options.
- Refill bag compatible with the Pro Choice Safety Gear dispenser station.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
EPOU	EACH	1	10
EPOC	EACH	1	10

MAINTENANCE

Before handling any earplugs, ensure hands are clean. Always check your earplugs and discard if damaged, worn or dirty. Silicone plugs can be washed if necessary. Single use ear plugs can cause health issues if used when dirty.

If kept clean and undamaged, silicone (reusable) ear plugs can be used many times over. Clean with mild soap/water and store in a case away from extreme heat and direct sunlight when not in use. On banded earplugs, clean and replace pads regularly as required.

APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



COMFORT



HI-VIS



HYGIENIC



SINGLE USE

PRODUCT DETAILS

Material:	PU Foam
Length:	2.8cm
Diameter:	1.2cm
Cord Length:	7.4cm
Weight:	3.1g
Colour:	Hi-Vis Orange Foam Blue Cord

TEST DATA

ATTENUATION TABLE (ATTENTION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	24	26.0	29.7	29.6	33.9	41.4	42.0
Standard Deviation	6.3	6.7	7.3	6.1	4.6	6.6	7.3
Mean-Minus-Standard Deviation Attenuations	17.7	19.3	22.4	23.5	29.3	34.8	34.7

SLC₈₀ Value is 27 (Class 5)

STANDARDS

CERTIFIED TO:

AS/NZS 1270:2002 Acoustic Hearing Protectors Class 5 SLC₈₀27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 112dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS