

HEARING PROTECTION

MAMBA SLIMLINE PRO SERIES CAP MOUNTED EARMUFF

PRODUCT DATA SHEET: HHEMMAMS



PRODUCT CODE:
HHEMMAMS



FEATURES AND BENEFITS

- Class 5 SLC₈₀ 26dB Attenuation.
- Hearing protection for noise levels to 110dB(A).
- Each Muff includes both 30 and 25mm wide slot adapters to suit all Safety Cap mounts.
- Dielectric earmuff and headband - manufactured with non-conductive material.
- Fully adjustable telescopic arms.
- Contemporary low profile design.
- High density sound reducing cup wall.
- High quality acoustic insulation foam.
- Premium soft touch ear cushions.
- Balanced clamping force for long duration wearer comfort.

PRODUCT DETAILS

Clamp Force: 9.8N
Materials of construction:
 - **Headband:** UPE/POM/PU Foam
 - **Cup:** ABS
 - **Insert:** PU Foam
 - **Cushion:** PU
Weight: 268 grams
Size: Standard One Size

APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



CARE INSTRUCTIONS

- Store in a cool, dry place.
- Avoid excessive UV exposure.
- Clean with mild detergent and water, allow to dry before use.
- Inspect headband and cup seals for wear and tear before use.

AVAILABLE IN

| PRODUCT CODE | COLOUR | UOM | MOQ | CTN QTY |
|--------------|-------------|------|-----|---------|
| HHEMMAMS | BLACK/GREEN | EACH | 1 | 20 |

TEST DATA

| ATTENUATION TABLE (ATTENTION IN DECIBELS) | | | | | | | |
|--|------|------|------|------|------|------|------|
| Frequency Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
| Mean Attenuation | 14.4 | 16.7 | 24.8 | 32.0 | 35.1 | 35.6 | 33.1 |
| Standard Deviation | 4.5 | 4.8 | 5.0 | 4.7 | 3.9 | 4.2 | 5.9 |
| Mean-Minus-Standard Deviation Attenuations | 9.9 | 11.9 | 19.8 | 27.3 | 31.2 | 31.4 | 27.2 |

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC₈₀ 26dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



PARAMOUNT SAFETY PRODUCTS AUSTRALIA
 12 FELLOWSHIP ROAD,
 GNANGARA, WA 6077
 TECH SUPPORT: 1300 275 820
 CUSTOMER SERVICE: 1300 770 723
 EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
 7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
 EAST TAMAKI, AUCKLAND 2013
 TECH SUPPORT: 0800 888 778
 CUSTOMER SERVICE: 0800 888 778
 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
 PARAMOUNTSAFETY.COM

PRO
 PRO CHOICE SAFETY GEAR
 FROM
PARAMOUNT
 SAFETY PRODUCTS