HEARING PROTECTION PYTHON® SLIMLINE HARD HAT EARMUFFS

PRODUCT DATA SHEET: HHEMPYTS

PRODUCT CODE: HHEMPYTS



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors Class 5 $\rm SLC_{80}31dB.$
- Hearing protection for noise levels to 116dB(A).
- Hi-vis yellow for visual identification.
- Robust steel wire construction for onsite demands.
- 25mm Cap attachment slot to suit all Pro Choice Safety Gear cap style hard hats.
- Compatible with Pro Choice Safety Gear hard hat brow guards (HHBGE/HHBGE-B).
- Contemporary low-profile design that withstands abuse without compromising on comfort.
- Solid, lightweight ear cup construction.
- High quality ear cushions.

CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

Order replacement hygiene kit for PRO Python Earmuffs - EMHKPYT.

APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM PARAMOUNT SAFETY PRODUCTS NEW ZEALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ



PRODUCT DETAILS

Weight: Clamping Force:	301g 12.5N
Colour:	Hi-Vis Yellow
Size:	Standard One Size

AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
HHEMPYTS	HVY	EACH	1	25

TEST DATA

ATTENUATION TABLE (ATTENTION IN DECIBELS)									
Frequency Hz	125	250	500	1000	2000	4000	8000		
Mean Attenuation	18.6	20.1	24.7	39.9	35.6	39.4	37.2		
Standard Deviation	3.7	2.7	3.0	2.5	2.2	3.2	5.2		
Mean-Minus-Standard Deviation Attenuations	14.9	17.4	24.4	37.4	33.4	36.2	32.0		

SLC₈₀ Value is 31 (Class 5)

STANDARDS

CERTIFIED TO:

AS/NZS 1270:2002 Acoustic Hearing Protectors -Class 5 SLC₈₀31dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 116dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.





PROCHOICESAFETYGEAR.COM PARAMOUNTSAFETY.COM

