# **PROTECTIVE HEADWEAR V9 VENTED HARD HAT WITH RATCHET HARNESS**

PRODUCT DATA SHEET: HHV9R-(COLOUR)















PRODUCT CODE:

## **FEATURES AND BENEFITS**

#### HELMET

- Certified to AS/NZS 1801:1997 Occupational Protective Helmets.
- Complete with 9 ventilation points.
- Lightweight ABS plastic vented hard hat.
- Replaceable cotton sweatband.
- 25mm moulded earmuff slots to accommodate ProChoice hearing protection.

#### HARNESS

- Fits all head sizes: 53cm 66cm.
- 6 point 25mm webbing ratchet harness.
- Quick and easy single hand adjustment ratchet whilst wearing the helmet
- Padded swivel feature for advanced positioning on back of the head.
- Replacement harness code: HHHR-V9

### **PRODUCT DETAILS**

Helmet Material:	ABS Plastic		
Harness Materials:	HDPE/Polyester		
Weight:	362g ± 2		
Colours:	Green, Blue, White, Fluoro Yellow, Yellow, Orange, Red		
Size:	53cm - 66cm		

### **APPLICATIONS**

Typical applications include but are not limited to:

Agriculture, Aviation, Automotive, Chemical manufacturing, Construction, Heavy engineering, Metal processing, Mining and Quarrying, Welding, Woodworking.

# **AVAILABLE IN**

PRODUCT CODE	UOM	MOQ	CTN QTY
HHV9R-(COLOUR)	EACH	1	20

Green (HHV9R-G), Blue (HHV9R-B), White (HHV9R-W), Fluoro Yellow (HHV9R-FY), Yellow (HHV9R-Y), Orange (HHV9R-O), Red (HHV9R-R).

#### PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD. GNANGARA, WA 6077 TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PROCHOICESAFETYGEAR.COM PARAMOUNT SAFETY PRODUCTS NEW ZEALAND 7 SIR WOOLF FISHER DRIVE, HIGHBROOK. EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ





## **CAREINSTRUCTIONS**

Upon issue, wearers name and date of issue should be printed on the label provided. Pro Choice Safety Gear hard hats should be inspected for any deterioration or damage prior to use. Pro Choice Safety Gear hard hats with excessive damage (cracks, colour distortion or deep abrasions) should be disposed of.

Entire hard hat, including harness, should be cleaned with warm soapy water (avoid any solvents) on a regular basis and sweatband replaced.

Industry recommends hard hat shell be replaced after 3 years of working life. Components of the hard hat harness may deteriorate during its normal working life, and as a result the harness should be replaced at intervals no longer than 2 years.

To extend your hard hat working life, avoid excessive exposure to UV and any solvents.

### HARD HAT PRINTING SERVICE

The need to distinguish workers in various occupations on a work site can be for safety or convenience. For example, having a safety officer readily identified by the colour of their hard hat can improve efficiencies; while being aware of who is a visitor or sub-contractor can improve security

To further enhance these advantages, ProChoice now offers a pad printing and a vinyl printing service that can customise hard hats before a customer takes delivery.

Speak to your ProChoice sales representative about adding value to your hard hat sales by utilising our pad printing or vinyl cut print service.

# **STANDARDS**

#### **CERTIFIED TO:**

AS/NZS 1801:1997 Occupational Protective Helmets To be used in conjunction with:

AS/NZS 1800:1998 Occupational Protective Helmets -Selection, Care and Use





