# HEARING PROTECTION

# **PYTHON® SLIMLINE HARD HAT EARMUFFS**

PRODUCT DATA SHEET: HHEMPYTS



PRODUCT CODE:



## **FEATURES AND BENEFITS**

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors Class 5  $\rm SLC_{80}31dB.$
- Hearing protection for noise levels to 110dB(A).
- Hi-vis yellow for visual identification.
- Robust steel wire construction for on-site demands.
- 25mm Cap attachment slot to suit all Pro Choice Safety Gear cap style hard hats.
- Contemporary low-profile design that withstands abuse without compromising on comfort.
- Solid, lightweight ear cup construction.
- High quality ear cushions.

### **AVAILABLE IN**

PRODUCT CODE	UOM	MOQ	CTNQTY	
HHEMPYTS	EACH	1	25	

### CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

# **APPLICATIONS**

Agriculture, Construction, Fire Protection, Forestry, Government, Emergency Services, Manufacturing, Military, Councils, Mining, Oil and Gas, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities.













## **PRODUCT DETAILS**

Weight: 301g
Clamping Force: 12.5N
Colour: Hi-Vis Yellow
Size: Standard One Size

## **TEST DATA**

ATTENUATION TABLE (ATTENTION IN DECIBELS)									
Frequency Hz	125	250	500	1000	2000	4000	8000		
Mean Attenuation	18.6	20.1	24.7	39.9	35.6	39.4	37.2		
Standard Deviation	3.7	2.7	3.0	2.5	2.2	3.2	5.2		
Mean-Minus-Standard Deviation Attenuations	14.9	17.4	24.4	37.4	33.4	36.2	32.0		

SLC<sub>80</sub> Value is 31 (Class 5)

### **STANDARDS**

#### CERTIFIED TO

**AS/NZS 1270:2002** Acoustic Hearing Protectors - Class 5  $SLC_{80}$ 31dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



#### PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM

#### PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EASTTAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ



