

RESPIRATORY GEAR MAXI MASK™ 2000 HALF FACE A1P2 RESPIRATOR KIT

PRODUCT DATA SHEET: HMA1P2



PRODUCT CODE:
HMA1P2



FEATURES AND BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- Durable thermoplastic rubber mask for superior fit.
- Retro reflective tape for improved wearer visibility.
- Enhanced bolstered four point cradle suspension harness for improved load bearing, better fit & comfort.
- Low resistance exhalation valve to reduce heat & moisture build up.
- Able to be worn under most welding helmets.
- Twin filter design provides a more balanced fit, lower breathing resistance & improves field of vision.
- Kit includes: 1 x mask, 2 x A1 filters, 2 x P2 pads & retainers, & 1 x resealable bag for hygienic storage.

AVAILABLE IN

PRODUCT CODE	QUANTITY	CARTON
HMA1P2	1 piece	24 pieces

PRODUCT DETAILS

Straps:	TPE (Thermoplastic Elastomer)
Harness:	4 Point Elastic Halo Harness
Filter Connection:	Bayonet
Filters:	A1 with P2 Pad filter
Mask Weight:	85g

CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.



WARNINGS AND USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

STANDARDS

CERTIFIED TO:

AS/NZS 1716:2012 Respiratory Protective Devices
Certified by SAI Global
To be used in conjunction with: AS/NZS 1715:2009 - Selection, use & maintenance of respiratory protective equipment



CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

RELATED PRODUCTS

PRODUCT CODE:
PCP2



P2 CARTRIDGE

PRODUCT CODE:
PCA1P2



A1P2 FILTERS TO SUIT
HMTPM

PRODUCT CODE:
PCABEK1



ABEK1 FILTERS

PRODUCT CODE:
PTCP3



PRESS TO CHECK™
P3 FILTERS

PRODUCT CODE:
HMA1P2-B



TRADIE'S & PAINTER'S
KIT - BUCKET

AUSTRALIA:
1800 770 723

ADELAIDE:
(613) 9764 9900
SA@PARAMOUNTSAFETY.COM.AU

MELBOURNE:
(613) 9764 9900
VIC@PARAMOUNTSAFETY.COM.AU

SYDNEY:
(612) 9601 3877
NSW@PARAMOUNTSAFETY.COM.AU

NEW ZEALAND:
0800 770 723
NZ@PARAMOUNTSAFETY.CO.NZ

BRISBANE:
(617) 3806 2699
QLD@PARAMOUNTSAFETY.COM.AU

PERTH:
(618) 9301 7888
WA@PARAMOUNTSAFETY.COM.AU

PROCHOICESAFETYGEAR.COM

