

ARAX PLATINUM GLOVE

PRODUCT CODE: APNPUD(SIZE)



FEATURES & BENEFITS

- EN388:2016 Cut Resistance Level "F".
- ASTM Cut Level 5.
- High level of cut resistance without sacrificing comfort or dexterity.
- Polyurethane (PU) & nitrile sand finish coated palm.
- Breathable Arax® liner.
- Form fitting for comfortable all day wear.
- Colour coded cuff for size identification.
- Anti-static.

APPLICATIONS

Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut & Abrasion Risks

PRODUCT DETAILS

- Material** : Engineered Composite 15 Gauge Seamless Arax® Fibre Liner interwoven with steel thread
- Dip** : Black Sand Finish PU/Nitrile Blend
- Cuff Type** : Knitted
- Colour** : Red, Black
- Sizes** : 7, 8, 9, 10, 11
- Qty/Pack** : 12 pairs
- Qty/Carton** : 120 pairs

PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	8.5cm +/-	21.5cm +/-
8	9.5cm +/-	22.5cm +/-
9	10.0cm +/-	23.5cm +/-
10	10.5cm +/-	24.5cm +/-
11	10.5cm +/-	25.5cm +/-

STANDARDS

CE CATEGORY:
 II Intermediary risk in accordance with:
 EN 420 / AS / NZS2161.2:2005 General Requirements
 EN 388:2016 Protection Against Mechanical Risks
Results - 4X44F
 ASTM F1790 Cut Level
Results - 5



PRODUCT CODE: APNPUD(SIZE)



CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

www.prosafetygear.com

PERTH
 T [618] 9301 7888
 F [618] 9301 7889
 E wa@paramountsafety.com.au

MELBOURNE
 T [613] 9764 9900
 F [613] 9764 9800
 E vic@paramountsafety.com.au

SYDNEY
 T [612] 9601 3877
 F [612] 9601 3899
 E nsw@paramountsafety.com.au

BRISBANE
 T [617] 3806 2699
 F [617] 3806 3266
 E qld@paramountsafety.com.au

ADELAIDE
 T [613] 9762 2500
 F [613] 9762 3500
 M 0424 504 802
 E sa@paramountsafety.com.au

NEW ZEALAND
 T [649] 525 8090
 F [649] 523 9773
 E nz@paramountsafety.co.nz